

COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

		MODEL DATA - I	FOR COMPRESSED	AIR					
1	Manufacturer: Kaishan Compressor USA								
	Model Number:	KROF-200-125 VSD		Date:	05/08/24				
2	Air-co	ooled X Water-cooled		Type:	Screw				
	Lubricated X Oil Free			# of Stages:	2				
3*	Full Load Operating Pressure ^b		125	psig					
4	Drive Motor Nominal Rating		200	hp					
5	Drive Motor Nominal Efficiency		95.4	percent					
6	Fan Motor Nominal Rating (if applicable)		0.5	hp					
7	Fan Motor Non	ninal Efficiency	69.5	percent					
8*	Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d					
	172.0		892	19.28					
	152.4		802	19.00					
	136.7		709	19.28					
	121.1		616	19.66					
	105.4		524	20.11					
9*	Total Package Input Power at Zero Flow c, d		0.0	kW					
10	Isentropic Effic	Isentropic Efficiency		%					
11	Specific Power (RW/100 ACFM)	Note: Y-Axis Scale, 10 to 3	0 400 500 600 Capacity (ACFM) 1 visual representation of the data in 15, +5kW/100acfm increments if neces [6, 0 to 25% over maximum capacity		900 1000				

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org





wember

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
 d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	Zero Flow Power
m ³ /min	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	17- 1070
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2 12/19 R3

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.