



## COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Fixed Speed

| MODEL DATA - FOR COMPRESSED AIR |                                                                                                                                                                            |              |                         |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------------------------|
| 1                               | Manufacturer: <b>Kaishan Compressor USA</b>                                                                                                                                |              |                         |
| 2                               | Model Number: <b>KROF-60-125</b>                                                                                                                                           |              | Date: <b>6/5/2026</b>   |
|                                 | <input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled<br><input type="checkbox"/> Oil-injected <input checked="" type="checkbox"/> Oil-free | Type:        | <b>Screw</b>            |
|                                 | # of Stages:                                                                                                                                                               |              | <b>2</b>                |
| 3*                              | Rated Capacity at Full Load Operating Pressure <sup>a, c</sup>                                                                                                             | <b>200.0</b> | acfm <sup>a, c</sup>    |
| 4                               | Full Load Operating Pressure <sup>b</sup>                                                                                                                                  | <b>125</b>   | psig <sup>b</sup>       |
| 5                               | Maximum Full Flow Operating Pressure <sup>c</sup>                                                                                                                          | <b>130</b>   | psig <sup>c</sup>       |
| 6                               | Drive Motor Nominal Rating                                                                                                                                                 | <b>60</b>    | hp                      |
| 7                               | Drive Motor Nominal Efficiency                                                                                                                                             | <b>93.6</b>  | percent                 |
| 8                               | Fan Motor Nominal Rating (if applicable)                                                                                                                                   | <b>2.65</b>  | hp                      |
| 9                               | Fan Motor Nominal Efficiency                                                                                                                                               | <b>71.6</b>  | percent                 |
| 10*                             | Total Package Input Power at Zero Flow <sup>c</sup>                                                                                                                        | <b>15.4</b>  | kW <sup>c</sup>         |
| 11                              | Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup>                                                                                  | <b>54.50</b> | kW <sup>d</sup>         |
| 12*                             | Specific Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>e</sup>                                                                               | <b>27.25</b> | kW/100 cfm <sup>c</sup> |
| 13                              | Isentropic Efficiency                                                                                                                                                      | <b>55.12</b> | Percent                 |

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: [www.cagi.org](http://www.cagi.org)

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Member

| Volume Flow Rate<br>at specified conditions |                            | Volume Flow Rate | Specific Energy<br>Consumption | No Load / Zero Flow<br>Power |
|---------------------------------------------|----------------------------|------------------|--------------------------------|------------------------------|
| $\text{m}^3 / \text{min}$                   | $\text{ft}^3 / \text{min}$ | %                | %                              | %                            |
| Below 0.5                                   | Below 17.6                 | +/- 7            | +/- 8                          | +/- 10%                      |
| 0.5 to 1.5                                  | 17.6 to 53                 | +/- 6            | +/- 7                          |                              |
| 1.5 to 15                                   | 53 to 529.7                | +/- 5            | +/- 6                          |                              |
| Above 15                                    | Above 529.7                | +/- 4            | +/- 5                          |                              |

ROT 030.2