			MOD		MDDECCED ATD		7
			MOD	EL DATA - FOR CO	MPRESSED AIR		_
	1 Manufacturer: Kaishan Compressor USA						
		Model Number: KRSP2-300-100			Date:	7/12/2021	
	2	X	Air-cooled	Water-cooled	Type:	Screw	_
			Oil-injected	Oil-free	# of Stages:	2	
		Rated C	apacity at Full I	oad Operating Pressure			
	3*	a, e			1666.0	acfm ^{a,e}	
	4	Full Load Operating Pressure ^b			100	psig ^b	
	5	Maximu	ım Full Flow Op	perating Pressure ^c	100	psig ^c	
	6	Drive Motor Nominal Rating			300	hp	_
	7	Drive M	lotor Nominal E	fficiency	96.2	percent	
	8	Fan Mo	tor Nominal Rat	ing (if applicable)	7.5 & 2.0	hp	
	9	Fan Motor Nominal Efficiency			91.0 & 87.5	percent	
	10*	Total Package Input Power at Zero Flow Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d			52.6	kW ^e	
	11				259.00	kW^d	
	12*		Package Input	Power at Rated Capacity g Pressure ^e	15.55	kW/100 cfm ^e	
	13	Isentropic Efficiency			85.49	Percent	
	*For mode	odels that are tested in the CAGI Performance Verification Program, these items are verified by the third party admini					inistrator.
	Consult C	CAGI website for a list of participants in the third party verification program: <u>www.cagi.org</u>					
NOTES		 a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions. b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet. c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power. d. Total package input power at other than reported operating points will vary with control strategy. e. Tolerance is specified in ISO 1217, Annex C, as shown in table below: NOTE: The terms "power" and "energy" are synonymous for purposes of this document. 					
Compressed Air	& Gas Institute	Γ	Vo	lume Flow Rate		Specific Energy	No Load / Zero Fl
			at sp	ecified conditions	Volume Flow Rate	Consumption	Power
			$\underline{m^3 / \min}$	<u>ft³ / min</u>	%	%	%
Men	nber		Below 0.5	Below 17.6	+/- 7	+/- 8	
			0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
			1.5 to 15	53 to 529.7	+/- 5	+/- 6	1